




GALVANISED CONCEALED PURLIN CLEAT

AUG26

Compliant with the requirements of AS1684. Designed and tested to AS1649.

G GALVANISED



APPLICATION

The VUETRADE Purlin Cleat is a strong and versatile bracket used to connect and provide tie-down of trusses to top plates or beams.

SPECIFICATION

VUETRADE Purlin Cleats are manufactured from G300 Z275 galvanised steel in 2.0 mm thickness.

FASTENERS FOR LONG SIDE (TRUSS / STUD)

Screws: VUETRADE Type 17 12G x 35mm Galvanised Connector Plate Screws, **OR:**

Nails: VUETRADE 30mm x 2.8mm Ø Galvanised Connector Plate Nails

FASTENERS FOR SHORT SIDE (WALL PLATE / BEAM)

Screws: VUETRADE Type 17 12G x 35mm Galvanised Connector Plate Screws **OR:**


VUETRADE Type 17 12G x 65mm Galvanised Connector Plate Screws as specified.

SIZES


Product Code	Nominal Dimensions	Ctn Qty
VPC4045	40 x 30 x 45mm	50
VPC4090	40 x 30 x 90 mm	50
VPC8090	80 x 30 x 90 mm	50

INSTALLATION GUIDE OF VPC8090

Install 4x VUETRADE Type 17 12G x 35mm Galvanised Connector Plate Screws to short side (See note 1)



Install 4x VUETRADE Type 17 12G x 35mm Galvanised Connector Plate Screws, OR 6x 30mm x 2.8mm Ø Galvanised Connector Plate Nails to long side



NOTES:

1. Fixing of Concealed Purlin Cleats to double top plate requires the use of 65mm screws. Refer to Tables 1 to 6 for relevant 65mm screw capacity data.
2. For other sizes of the Concealed Purlin Cleat, use the recommended number of fixings listed in the Design Capacity Data..





GALVANISED CONCEALED PURLIN CLEAT

AUG26

DESIGN CAPACITY DATA




Table 1: Concealed Purlin Cleats **VPC8090**
with 4x 12Gx35mm screw fixing of Long side
(Truss / Stud)



Fixing on Short side (Plate/Beam)	Design Capacity for Timber Joint Groups, kN		
	JD3	JD4	JD5
4x 12G x 35mm screws	11.2	8.4	6.7
4x 12G x 65mm screws	13.8	9.8	6.9



Table 4: Concealed Purlin Cleats **VPC8090**
with 10x 30x2.8mm Ø nail fixing of Long side
(Truss / Stud)



Fixing on Short side (Plate/Beam)	Design Capacity for Timber Joint Groups, kN		
	JD3	JD4	JD5
4x 12G x 35mm screws	9.0	6.4	5.3
4x 12G x 65mm screws	9.0	6.4	5.3



Table 2: Concealed Purlin Cleats **VPC4090**
with 2x 12Gx35mm screw fixing of Long side
(Truss / Stud)

Fixing on Short side (Plate/Beam)	Design Capacity for Timber Joint Groups, kN		
	JD3	JD4	JD5
2x 12G x 35mm screws	5.6	4.2	3.4
2x 12G x 65mm screws	6.9	4.9	3.5



Table 5: Concealed Purlin Cleats **VPC4090**
with 5x 30x2.8mm Ø nail fixing of Long side
(Truss / Stud)

Fixing on Short side (Plate/Beam)	Design Capacity for Timber Joint Groups, kN		
	JD3	JD4	JD5
2x 12G x 35mm screws	4.5	3.2	2.6
2x 12G x 65mm screws	4.5	3.2	2.6



Table 3: Concealed Purlin Cleats **VPC4045**
with 1x 12Gx35mm screw fixing of Long side
(Truss / Stud)



Fixing on Short side (Plate/Beam)	Design Capacity for Timber Joint Groups, kN		
	JD3	JD4	JD5
2x 12G x 35mm screws	3.5	2.5	1.7
2x 12G x 65mm screws	3.5	2.5	1.7



Table 6: Concealed Purlin Cleats **VPC4045**
with 2x 30x2.8mm Ø nail fixing of Long side
(Truss / Stud)



Fixing on Short side (Plate/Beam)	Design Capacity for Timber Joint Groups, kN		
	JD3	JD4	JD5
2x 12G x 35mm screws	1.8	1.3	1.1
2x 12G x 65mm screws	1.8	1.3	1.1

NOTES:

- Design capacities in the above tables are based on installing the above listed fasteners through pre-punched holes.
- Modification factors k_1 used in capacity tables above is for wind uplift and is adopted from AS1720.1-2010.
- Design capacities in the above tables are based on Category 1 joints where it is applicable for failures that would be unlikely to affect an area of greater than 25m². For Category 2 and Category 3 joints, design capacities from the table are multiplied by 0.941 and 0.882 respectively.
- Capacities in above tables can be doubled when a pair of cleats are installed.
- The longer screw 12G x 65mm specified in the tables above are required for double top plates, or to beams/lintels for higher capacity.
- VUETRADE strongly recommends all timber connector products are installed as per the installation instructions on the relevant Technical Data Sheet, using the recommended type and quantity of fasteners.







GALVANISED CONCEALED PURLIN CLEAT



AUG26

ALTERNATE USAGE OF CONCEALED PURLIN CLEAT

Rafter/Truss to top plate



Stud to top/bottom plate



Truss/Rafter/Purlin to beam / lintel

