VUETRADE for the builder

Timber Connectors
Technical Data Sheet

GALVANISED CENTRE BLADE POST SUPPORTS

OCT26

Compliant with the requirements of AS1684 and AS1720.

G GALVANISED


BOLTED TO CONCRETE



CAST INTO CONCRETE







APPLICATION

Centre Blade Post Supports are brackets used for fixing timber posts to concrete or timber bases, with the 'hidden' blade providing a neat finish.

SPECIFICATION

VUETRADE Galvanised Centre Blade Post Supports are manufactured in G300 steel and corrosion protected with Hot Dipped Galvanised.


FASTENERS

Saddle: 2x Zinc-Nickel Coated VUEBOLT or appropriate M10 bolts with hex nuts

Base: 2x M10 concrete bolts or equivalent

SIZES

Product Code	Height (mm)	Box Qty
VBLPS125	125	10
VBLPS300	300	10




technical@bellevuegroup.com.au
1300 850 520 www.vuetrade.com


VUETRADE Timber Connectors is a division of **Bellevue Group Australasia**.
Bellevue Group Australasia are continuously working to develop and improve our product range. We reserve the right to change specifications, etc. without notice.

GALVANISED CENTRE BLADE POST SUPPORTS

OCT26

INSTALLATION GUIDE AND BOLT FIXING SCHEDULE





NOTES:

1. Embedment depth of VUETRADE Post Support should be determined and calculated by a Structural Engineer to achieve the reported design load. This usually depends on the type of concrete used, aggregate ratio etc.
2. 75mm clearance must be provided to conform to the requirements set out by AS3660.1:2014 - *Termite management, Part 1: New building work.*

DESIGN CAPACITY DATA

Table 1: Design Capacity of Centre Blade Post Support in different joint groups

Load Case	Design Capacity, Ndj (kN)		
	JD3	JD4	JD5
Uplift capacity	6.1	4.9	4.3

NOTES:

1. Design capacity in Table 1 applies to VUETRADE Centre Blade Post Supports where 2x M10 VUEBOLTS / appropriate bolts are installed and tightly fastened with hex nuts.
2. Timber posts must have minimum dimensions of 90mm by 90mm section and shall be installed flat to the base of the post support.
3. Footings by others.

   a. Design capacities for post supports bolted or cast into concrete assumed that there is sufficient anchorage to resist wind uplift.

   b. Design capacity of this post support may be limited by the withdrawal tensile capacity of concrete bolts used to fasten post support to concrete ground. Ensure that suitable concrete bolts are used for above design capacities to be valid.
4. Design capacities in the above table are for wind uplift (vertical force direction) only and are obtained under strict in-house test conditions defined by AS1649:2025 – *Timber - Methods of test for mechanical fasteners and connectors* & uplift capacity requirements outlined in AS1720.1-2010 – *Timber structures, Part 1: Design methods.*
5. VUETRADE Post Supports should only be used to resist wind uplift / dead load as specified in the TDS and should not be assumed to provide lateral stability. Sufficient bracing should be provided and approved by a structural engineer for lateral stability.
7. Design capacity in Table 1 are based on Category 1 joints where it is applicable for failures that would be unlikely to affect an area of greater than 25m2. For Category 2 and Category 3 joints, design capacities in this table are modified by multiplying 0.941 and 0.882 respectively.



technical@bellevuegroup.com.au
1300 850 520 www.vuetrade.com

VUETRADE Timber Connectors is a division of **Bellevue Group Australasia**.
Bellevue Group Australasia are continuously working to develop and improve our product range. We reserve the right to change specifications, etc. without notice.