VUETRADE for the builder

Timber Connectors
Technical Data Sheet

STAINLESS STEEL HALF STIRRUP POST SUPPORTS

OCT26

Compliant with the requirements of AS1684 and AS1720.

304 STAINLESS STEEL

316 STAINLESS STEEL


BOLTED TO CONCRETE



CAST INTO CONCRETE







APPLICATION

VUETRADE Stainless Steel Half Stirrup Post Supports are typically used when builders only have access to bolt one side of the timber post. Installed either by bolting to the concrete or by casting into wet concrete, these post supports offer high resistance to rust specifically for applications near the coast.

SPECIFICATION

VUETRADE Stainless Steel Half Stirrup Post Supports are available to be manufactured in two materials, SS304 and SS316.

FASTENERS

Saddle: 2x Stainless Steel VUEBOLT or appropriate M12 bolts with hex nuts

Base: 2x stainless steel M12 concrete bolts or equivalent

Only use stainless steel fasteners (bolts) with stainless steel post support, usage of other steel materials may lead to bimetallic corrosion.

SIZES

Product Code	Material	Height (mm)	Box Qty
VHSPS125SS	SS304	125	10
VHSPS200SS304	SS304	200	10
VHSPS300SS304	SS304	300	10
VHSPS125SS316	SS316	125	10
VHSPS200SS316	SS316	200	10
VHSPS300SS316	SS316	300	10

MATERIAL SPECIFICATION

Stainless Steel 304

Composition: 18 % Chromium, 8% Nickel

Corrosion resistance: Good resistance to oxidation and corrosion, but weak against acidic environment

Stainless Steel 316

Composition: 16% Chromium, 10% Nickel, 2% Molybdenum

Corrosion resistance: Superior corrosion resistance against acidic/high chloride environments

NOTE:

'Tea-staining' is a cosmetic issue with some VUETRADE Stainless Steel Post Supports (more prevalent in SS304) but this does not affect the structural integrity or material lifetime of the post support.


technical@bellevuegroup.com.au
1300 850 520 www.vuetrade.com


VUETRADE Timber Connectors is a division of **Bellevue Group Australasia**.
Bellevue Group Australasia are continuously working to develop and improve our product range. We reserve the right to change specifications, etc. without notice.

STAINLESS STEEL HALF STIRRUP POST SUPPORTS

OCT26

INSTALLATION GUIDE AND BOLT FIXING SCHEDULE





NOTES:

1. Embedment depth of VUETRADE Post Support should be determined and calculated by a Structural Engineer in order to achieve the reported design load. This usually depends on the type of concrete used, aggregate ratio etc.
2. 75mm clearance must be provided to conform to the requirements set out by AS3660.1:2014 - *Termite management, Part 1: New building work.*

DESIGN CAPACITY DATA

Table 1: Design capacities of Stainless Steel Half Stirrup Post Support on various timber joint groups


Load Case	Design Capacity, Ndj (kN)					
	J3	J4	J5	JD3	JD4	JD5
Uplift capacity	6.3	5.0	4.3	7.9	6.3	5.5

NOTES:

1. Design capacity in Table 1 applies to VUETRADE Stainless Steel Half Stirrup Post Supports where 2x M12 SS VUEBOLTS / appropriate bolts are installed and tightly fastened with hex nuts.
2. Timber posts must have minimum dimensions of 90mm by 90mm section and shall be installed flat to the base of the post support.
3. Footings by others.

   a. Design capacities for post supports bolted or cast into concrete assumed that there is sufficient anchorage to resist wind uplift.

   b. Design capacity of this post support may be limited by the withdrawal tensile capacity of concrete bolts used to fasten post support to concrete ground. Ensure that suitable concrete bolts are used for above design capacities to be valid.
4. Design capacities in the above table are for wind uplift (vertical force direction) only and are obtained under strict in-house test conditions defined by AS1649:2025 – *Timber - Methods of test for mechanical fasteners and connectors* & uplift capacity requirements outlined in AS1720.1-2010 – *Timber structures, Part 1: Design methods*.
5. VUETRADE Post Supports should only be used to resist wind uplift / dead load as specified in the TDS and should not be assumed to provide lateral stability. Sufficient bracing should be provided and approved by a structural engineer for lateral stability.
7. Design capacity in Table 1 are based on Category 1 joints where it is applicable for failures that would be unlikely to affect an area of greater than 25m2. For Category 2 and Category 3 joints, design capacities in this table are modified by multiplying 0.941 and 0.882 respectively.



technical@bellevuegroup.com.au
1300 850 520 www.vuetrade.com

VUETRADE Timber Connectors is a division of **Bellevue Group Australasia**.
Bellevue Group Australasia are continuously working to develop and improve our product range. We reserve the right to change specifications, etc. without notice.